

Type	MCB100 (UE)																	
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	L2	L3	β Angle			
	kg	m/s	mm		A	kW	r/min	Hz	N·m		mm	mm	mm	mm	°			
630-1.0A	630	1.0	320	4×Φ8×11	11	4.0	119	31.7	320	32	205	185	7.5	39	95			
630-1.5A	630	1.5		4×Φ8×11	14	6.0	179	47.7	320	32								
630-1.6A	630	1.6		4×Φ8×11	16	6.4	191	50.9	320	32								
630-1.75A	630	1.75		4×Φ8×11	16	7.0	209	55.7	320	32								
800-1.0A	800	1.0	320	5×Φ8×11	13	5.1	119	31.7	410	32	205	185	7.5	39		95		
800-1.5A	800	1.5		5×Φ8×11	18	7.7	179	47.7	410	32								
800-1.6A	800	1.6		5×Φ8×11	21	8.2	191	50.9	410	32								
800-1.75A	800	1.75		5×Φ8×11	21	9.0	209	55.7	410	32								
630-1.0B	630	1.0	400	4×Φ8×11	10	4.0	95	25.3	400	32	205	185	7.5	39			95	
630-1.5B	630	1.5		4×Φ8×11	13	6.0	143	38.1	400	32								
630-1.6B	630	1.6		4×Φ8×11	16	6.4	153	40.8	400	32								
630-1.75B	630	1.75		4×Φ8×11	16	7.0	167	44.5	400	32								
800-1.0B	800	1.0	400	5×Φ8×11	12	5.1	95	25.3	510	32	238	218	/	47				95
800-1.5B	800	1.5		5×Φ8×11	18	7.6	143	38.1	510	32								
800-1.6B	800	1.6		5×Φ8×11	20	8.2	153	40.8	510	32								
800-1.75B	800	1.75		5×Φ8×11	20	8.9	167	44.5	510	32								
1000-1.0	1000	1.0	400	6×Φ8×11	15	6.4	95	25.3	640	32	238	218	/	47	95			
1000-1.5	1000	1.5		6×Φ8×11	23	9.6	143	38.1	640	32								
1000-1.6	1000	1.6		6×Φ8×11	26	10.3	153	40.8	640	32								
1000-1.75	1000	1.75		6×Φ8×11	26	11.2	167	44.5	640	32								

Type	MCB200 (UE)										
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	β Angle
	kg	m/s	mm		A	kW	r/min	Hz	N·m		°
800-1.0	800	1.0	400	5×Φ8×11	12	5.1	95	31.7	510	40	95
800-1.5	800	1.5		5×Φ8×11	18	7.6	143	47.7	510	40	
800-1.6	800	1.6		5×Φ8×11	20	8.2	153	51.0	510	40	
800-1.75	800	1.75		5×Φ8×11	20	8.9	167	55.7	510	40	
1000-1.0A	1000	1.0	400	6×Φ8×11	15	6.4	95	31.7	640	40	
1000-1.5A	1000	1.5		6×Φ8×11	23	9.6	143	47.7	640	40	
1000-1.6A	1000	1.6		6×Φ8×11	26	10.3	153	51.0	640	40	
1000-1.75A	1000	1.75		6×Φ8×11	26	11.2	167	55.7	640	40	
1150-1.0A	1150	1.0	400	6×Φ8×11	17	7.3	95	31.7	730	40	
1150-1.5A	1150	1.5		6×Φ8×11	30	10.9	143	47.7	730	40	
1150-1.6A	1150	1.6		6×Φ8×11	30	11.7	153	51.0	730	40	
1150-1.75A	1150	1.75		6×Φ8×11	30	12.8	167	55.7	730	40	
1250-1.0	1250	1.0	400	7×Φ8×11	20	8.0	95	31.7	800	40	
1250-1.5	1250	1.5		7×Φ8×11	30	12.0	143	47.7	800	40	
1250-1.6	1250	1.6		7×Φ8×11	34	12.8	153	51.0	800	40	
1250-1.75	1250	1.75		7×Φ8×11	34	14.0	167	55.7	800	40	
1000-1.0B	1000	1.0	480	6×Φ8×11	16	6.4	80	26.7	760	40	
1000-1.5B	1000	1.5		6×Φ8×11	23	9.5	119	39.7	760	40	
1000-1.6B	1000	1.6		6×Φ8×11	27	10.1	127	42.3	760	40	
1000-1.75B	1000	1.75		6×Φ8×11	27	11.1	139	46.3	760	40	
1150-1.0B	1150	1.0	480	6×Φ8×11	19	7.4	80	26.7	880	40	
1150-1.5B	1150	1.5		6×Φ8×11	30	11.0	119	39.7	880	40	
1150-1.6B	1150	1.6		6×Φ8×11	30	11.7	127	42.3	880	40	
1150-1.75B	1150	1.75		6×Φ8×11	30	12.8	139	46.3	880	40	

Type	MCB300 (UE)										
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	β Angle
	kg	m/s	mm		A	kW	r/min	Hz	N·m		°
1350-1.0	1350	1.0	480	7× Φ 8×12	21	8.6	80	26.7	1030	40	95
1350-1.5	1350	1.5		7× Φ 8×12	30	12.8	119	39.7	1030	40	
1350-1.6	1350	1.6		7× Φ 8×12	36	13.7	127	42.3	1030	40	
1350-1.75	1350	1.75		7× Φ 8×12	36	15.0	139	46.3	1030	40	
1600-1.0	1600	1.0	480	8× Φ 8×12	25	10.5	80	26.7	1250	40	
1600-1.5	1600	1.5		8× Φ 8×12	35	15.6	119	39.7	1250	40	
1600-1.6	1600	1.6		8× Φ 8×12	43	16.6	127	42.3	1250	40	
1600-1.75	1600	1.75		8× Φ 8×12	43	18.2	139	46.3	1250	40	