

Type	MCK100 (UE)																	
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	L2	β Angle				
	kg	m/s	mm		A	kW	r/min	Hz	N·m		mm	mm	mm	°				
320-1.0	320	1.0	320	3×Φ8×12	5	2.2	119	23.8	180	24	235	52	163	95				
320-1.6	320	1.6		3×Φ8×12	8	3.6	191	38.2	180	24								
450-1.0	450	1.0	320	4×Φ8×12	7	2.7	119	23.8	220	24	235	52	163		95			
450-1.6	450	1.6		4×Φ8×12	11	4.4	191	38.2	220	24								
630-1.0	630	1.0	320	5×Φ8×12	10	3.9	119	23.8	310	24	245	57	163			95		
630-1.6	630	1.6		5×Φ8×12	16	6.2	191	38.2	310	24								
800-1.0	800	1.0	320	6×Φ8×12	13	5.1	119	23.8	410	24	245	61	163				95	
800-1.6	800	1.6		6×Φ8×12	22	8.2	191	38.2	410	24								
1000-1.0	1000	1.0	320	7×Φ8×12	16	6.4	119	23.8	510	24	295	66	204					95
1000-1.6	1000	1.6		7×Φ8×12	26	10.2	191	38.2	510	24								

Type	MCK200 (UE)													
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	β Angle	
	kg	m/s	mm		A	kW	r/min	Hz	N·m		mm	mm	°	
Roping 1:1														
400-1.0	400	1.0	400	5×Φ10×15	8	2.6	48	12.8	520	32	280	69.5	95	
400-1.6	400	1.6		5×Φ10×15	11	4.1	76	20.3	520	32				
450-1.0	450	1.0	400	5×Φ10×15	9	3	48	12.8	590	32	280	69.5		
450-1.6	450	1.6		5×Φ10×15	12	4.7	76	20.3	590	32				
500-1.0	500	1.0	400	5×Φ10×15	10	3.3	48	12.8	650	32	280	69.5		
500-1.6	500	1.6		5×Φ10×15	14	5.2	76	20.3	650	32				
550-1.0	550	1.0	400	6×Φ10×15	11	3.5	48	12.8	700	32	292	75.5		
550-1.6	550	1.6		6×Φ10×15	15	5.6	76	20.3	700	32				
630-1.0	630	1.0	400	6×Φ10×15	13	4	48	12.8	800	32	292	75.5		
630-1.6	630	1.6		6×Φ10×15	17	6.4	76	20.3	800	32				
Roping 2:1														
630-1.0	630	1.0	400	4×Φ10×15	10	4.2	95	25.3	420	32	280	69.5		
630-1.6	630	1.6		4×Φ10×15	16	6.7	153	40.8	420	32				
630-2.0	630	2.0		4×Φ10×15	18	8.4	191	50.9	420	32				
800-1.0	800	1.0	400	5×Φ10×15	12	5.2	95	25.3	520	32	280	69.5		
800-1.6	800	1.6		5×Φ10×15	20	8.3	153	40.8	520	32				
800-2.0A	800	2.0		5×Φ10×15	23	10.4	191	50.9	520	32				
800-2.5A	800	2.5		6×Φ10×15	28	13.0	239	63.7	520	32			292	75.5
1000-1.0	1000	1.0		5×Φ10×15	15	6.5	95	25.3	650	32			280	69.5
1000-1.6	1000	1.6	5×Φ10×15	26	10.4	153	40.8	650	32					
1000-2.0A	1000	2.0	5×Φ10×15	28	13	191	50.9	650	32					
1000-2.5A	1000	2.5	6×Φ10×15	34	16.3	239	63.7	650	32	292	75.5			
1150-1.0A	1150	1.0	400	5×Φ10×15	17	7.5	95	25.3	750	32	280	69.5		
1150-1.6A	1150	1.6		6×Φ10×15	29	12.0	153	40.8	750	32			292	75.5
1150-2.0A	1150	2.0		6×Φ10×15	33	15.0	191	50.9	750	32				
800-2.0B	800	2.0	450	5×Φ10×15	23	10.5	170	45.3	590	32	280	69.5		
800-2.5B	800	2.5		5×Φ10×15	29	13.1	212	56.5	590	32				
1000-2.0B	1000	2.0	450	5×Φ10×15	28	13.0	170	45.3	730	32	280	69.5		
1000-2.5B	1000	2.5		6×Φ10×15	36	16.2	212	56.5	730	32			292	75.5
1150-1.0B	1150	1.0	450	5×Φ10×15	18	7.1	85	22.7	800	32	280	69.5		
1150-1.6B	1150	1.6		6×Φ10×15	30	11.4	136	36.3	800	32			292	75.5

Type	MCK200E (UE)												
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	β Angle
	kg	m/s	mm		A	kW	r/min	Hz	N·m		mm	mm	°
Roping 1:1													
550-1.0	550	1.0	400	6×Φ10×15	11	3.5	48	12.8	700	32	272	75.5	95
550-1.6	550	1.6		6×Φ10×15	15	5.6	76	20.3	700	32			
630-1.0	630	1.0	400	6×Φ10×15	13	4	48	12.8	800	32	272	75.5	
630-1.6	630	1.6		6×Φ10×15	17	6.4	76	20.3	800	32			
Roping 2:1													
630-1.0	630	1.0	400	4×Φ10×15	10	4.2	95	25.3	420	32	260	69.5	95
630-1.6	630	1.6		4×Φ10×15	16	6.7	153	40.8	420	32			
630-2.0	630	2.0		4×Φ10×15	18	8.4	191	50.9	420	32			
800-1.0	800	1.0	400	5×Φ10×15	12	5.2	95	25.3	520	32	260	69.5	
800-1.6	800	1.6		5×Φ10×15	20	8.3	153	40.8	520	32			
800-2.0	800	2.0		5×Φ10×15	23	10.4	191	50.9	520	32			
800-2.5	800	2.5		6×Φ10×15	28	13.0	239	63.7	520	32			
1000-1.0A	1000	1.0	400	5×Φ10×15	15	6.5	95	25.3	650	32	260	69.5	
1000-1.6A	1000	1.6		5×Φ10×15	26	10.4	153	40.8	650	32			
1000-2.0A	1000	2.0		5×Φ10×15	28	13.0	191	50.9	650	32			
1000-2.5A	1000	2.5		6×Φ10×15	34	16.3	239	63.7	650	32			
1150-1.0A	1150	1.0	400	5×Φ10×15	17	7.5	95	25.3	750	32	260	69.5	
1150-1.6A	1150	1.6		6×Φ10×15	29	12.0	153	40.8	750	32			
1150-2.0A	1150	2.0		6×Φ10×15	33	15.0	191	50.9	750	32			
1250-1.0	1250	1.0	400	6×Φ10×15	20	8.0	95	25.3	800	32	272	75.5	
1250-1.6	1250	1.6		6×Φ10×15	30	12.8	153	40.8	800	32			
1250-2.0	1250	2.0		6×Φ10×15	38	16.0	191	50.9	800	32			
1000-1.0B	1000	1.0	450	5×Φ10×15	15	6.5	85	22.7	730	32	260	69.5	
1000-1.6B	1000	1.6		5×Φ10×15	25	10.4	136	36.3	730	32			
1000-2.0B	1000	2.0		5×Φ10×15	28	13.0	170	45.3	730	32			
1000-2.5B	1000	2.5		6×Φ10×15	36	16.2	212	56.5	730	32			
1150-1.0B	1150	1.0	450	5×Φ10×15	18	7.1	85	22.7	800	32	260	69.5	
1150-1.6B	1150	1.6		6×Φ10×15	30	11.4	136	36.3	800	32			

Type MCK300 (UE)																	
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	L2	β Angle			
	kg	m/s	mm		A	kW	r/min	Hz	N-m		mm	mm	mm	°			
Roping 1:1																	
630-1.0A	630	1.0	400	6×Φ10×15	13	4.0	48	12.8	800	32	345	86	211	95			
630-1.6A	630	1.6		6×Φ10×15	17	6.4	76	20.3	800	32							
800-1.0A	800	1.0	400	7×Φ10×15	17	5.2	48	12.8	1040	32	345	86	211				
800-1.6A	800	1.6		7×Φ10×15	25	9.1	84	22.4	1040	32							
630-1.0B	630	1.0	450	6×Φ10×15	14	4.0	42	11.2	900	32	345	86	211				
630-1.6B	630	1.6		6×Φ10×15	19	7.0	74	19.7	900	32							
800-1.0B	800	1.0	450	7×Φ10×15	16	5.1	42	11.2	1170	32	345	86	211				
800-2.0B	800	2.0		7×Φ10×15	24	10.4	85	22.7	1170	32							
Roping 2:1																	
1250-1.0	1250	1.0	400	6×Φ10×15	20	8.0	95	25.3	800	32	345	86	211	95			
1250-1.6	1250	1.6		6×Φ10×15	30	12.8	153	40.8	800	32							
1250-2.0	1250	2.0		6×Φ10×15	38	16.0	191	50.9	800	32							
1350-1.0A	1350	1.0	400	7×Φ10×15	21	8.6	95	25.3	860	32	345	86	211				
1350-1.6A	1350	1.6		7×Φ10×15	35	13.8	153	40.8	860	32							
1350-2.0A	1350	2.0		7×Φ10×15	40	17.2	191	50.9	860	32							
1600-1.0A	1600	1.0	400	7×Φ10×15	24	10.3	95	25.3	1040	32	345	86	211				
1600-1.6A	1600	1.6		8×Φ10×15	40	16.7	153	40.8	1040	32							
1600-2.0A	1600	2.0		8×Φ10×15	45	20.8	191	50.9	1040	32					360	93.5	211
1600-2.5A	1600	2.5		8×Φ10×15	55	26.0	239	63.7	1040	32							
1350-1.0B	1350	1.0	450	7×Φ10×15	22	8.6	85	22.7	970	32	345	86	211				
1350-1.6B	1350	1.6		7×Φ10×15	35	13.8	136	36.3	970	32							
1350-2.0B	1350	2.0		7×Φ10×15	38	17.3	170	45.3	970	32							
1350-2.5B	1350	2.5		7×Φ10×15	49	21.5	212	56.5	970	32							
1600-1.0B	1600	1.0	450	7×Φ10×15	24	10.4	85	22.7	1170	32	372	91	233				
1600-1.6B	1600	1.6		8×Φ10×15	40	16.7	136	36.3	1170	32							
1600-2.0B	1600	2.0		8×Φ10×15	45	20.8	170	45.3	1170	32							
1600-2.5B	1600	2.5		8×Φ10×15	55	26	212	56.5	1170	32							

Type	MCK500 (UE)													
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	L	L1	β Angle	
	kg	m/s	mm		A	kW	r/min	Hz	N·m		mm	mm	°	
Roping 1:1														
800-1.0	800	1.0	480	6×Φ12×17	18	5.2	40	13.3	1250	40	350	91	95	
800-2.0	800	2.0		6×Φ12×17	26	10.5	80	26.7	1250	40				
1000-1.0	1000	1.0	480	7×Φ12×17	23	6.5	40	13.3	1560	40	350	91		
1000-2.0	1000	2.0		7×Φ12×17	30	13.1	80	26.7	1560	40				
800-1.0	800	1.0	520	6×Φ12×17	18	4.9	37	12.3	1270	40	350	91		
800-1.6	800	1.6		6×Φ12×17	26	7.8	59	19.7	1270	40				
800-2.0	800	2.0		6×Φ12×17	26	9.7	73	24.3	1270	40				
1000-1.0	1000	1.0	520	7×Φ12×17	23	6.2	37	12.3	1590	40	350	91		
1000-1.6	1000	1.6		7×Φ12×17	32	9.8	59	19.7	1590	40				
1000-2.0	1000	2.0		7×Φ12×17	32	12.2	73	24.3	1590	40				
Roping 2:1														
1600-1.0A	1600	1.0	480	6×Φ12×17	25	10.5	80	26.7	1250	40	350	91		95
1600-1.6A	1600	1.6		6×Φ12×17	42	16.6	127	42.3	1250	40				
1600-2.0A	1600	2.0		6×Φ12×17	47	20.8	159	53.0	1250	40				
1600-2.5A	1600	2.5		6×Φ12×17	57	26.0	199	66.3	1250	40				
2000-1.0A	2000	1.0	480	7×Φ12×17	31	13.1	80	26.7	1560	40	350	91		
2000-1.6A	2000	1.6		7×Φ12×17	51	20.7	127	42.3	1560	40				
2000-2.0A	2000	2.0		7×Φ12×17	59	26.0	159	53.0	1560	40				
2000-2.5A	2000	2.5		8×Φ12×17	71	32.5	199	66.3	1560	40			365	
2500-1.0A	2500	1.0	480	8×Φ12×17	38	16.3	80	26.7	1950	40	365	98.5		
2500-1.6A	2500	1.6		8×Φ12×17	66	25.9	127	42.3	1950	40				
2500-2.0A	2500	2.0		8×Φ12×17	71	32.5	159	53.0	1950	40				
2500-2.5A	2500	2.5		9×Φ12×17	83	40.6	199	66.3	1950	40			390	

Type	MCK500 (UE)										
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	β Angle
	kg	m/s	mm		A	kW	r/min	Hz	N·m		°
3000-1.0A	3000	1.0	480	8×Φ12×17	46	19.6	80	26.7	2340	40	95
3000-1.6A	3000	1.6		8×Φ12×17	78	31.1	127	42.3	2340	40	
3000-2.0A	3000	2.0		9×Φ12×17	83	39.0	159	53.0	2340	40	
3000-2.5A	3000	2.5		9×Φ12×17	108	48.8	199	66.3	2340	40	
3000-1.0B	3000	1.0	520	8×Φ13×18	43	18.2	73	24.3	2380	40	
3000-1.6B	3000	1.6		8×Φ13×18	75	29.4	118	39.3	2380	40	
3000-2.0B	3000	2.0		8×Φ13×18	82	36.6	147	49.0	2380	40	
3000-2.5B	3000	2.5		8×Φ13×18	106	45.9	184	61.3	2380	40	

Type	MGK520 (UE)											
Spec.	Load	Elv. Speed	Sheave Diam.	Sheave Groove	Current	Power	Speed	Freq.	Torque	Poles	β Angle	
	kg	m/s	mm		A	kW	r/min	Hz	N·m		°	
Roping 1:1												
1600-1.0	1600	1.0	520	8×Φ13×19	26	10.5	37	14.8	2700	48	105	
1600-1.5	1600	1.5	520	8×Φ13×19	38	15.6	55	22.0	2700	48		
1600-1.75	1600	1.75	520	8×Φ13×19	42	18.1	64	25.6	2700	48		
1600-2.0	1600	2.0	520	8×Φ13×19	47	20.6	73	29.2	2700	48		
1600-2.5	1600	2.5	520	8×Φ13×19	57	26.0	92	36.8	2700	48		
1600-3.0	1600	3.0	520	8×Φ13×19	67	31.1	110	44.0	2700	48		
Roping 2:1												
3000-1.0	3000	1.0	520	8×Φ13×19	45	19.3	73	29.2	2530	48	105	
3000-1.6	3000	1.6	520	8×Φ13×19	75	31.3	118	47.2	2530	48		
3000-1.75	3000	1.75	520	8×Φ13×19	75	34.2	129	51.6	2530	48		
3000-2.0	3000	2.0	520	8×Φ13×19	85	38.9	147	58.8	2530	48		
3000-2.5	3000	2.5	520	8×Φ13×19	106	48.7	184	73.6	2530	48		
3000-3.0	3000	3.0	520	8×Φ13×19	128	58.3	220	88.0	2530	48		
3500-1.0	3500	1.0	520	8×Φ13×19	52	22.5	73	29.2	2950	48		
3500-1.6	3500	1.6	520	8×Φ13×19	87	36.5	118	47.2	2950	48		
3500-1.75	3500	1.75	520	8×Φ13×19	87	39.9	129	51.6	2950	48		
3500-2.0	3500	2.0	520	8×Φ13×19	99	45.4	147	58.8	2950	48		
3500-2.5	3500	2.5	520	8×Φ13×19	124	56.8	184	73.6	2950	48		
3500-3.0	3500	3.0	520	8×Φ13×19	150	68.0	220	88.0	2950	48		
Roping 6:1												
10000-0.5	10000	0.5	520	8×Φ13×19	87	34.0	110	44.0	2950	48		As required
10000-1.0	10000	1.0	520	8×Φ13×19	150	68.0	220	88.0	2950	48		